

Creating a consistency query

Principle

A consistency query is used to find anomalies in the data. Technically, the same result could be obtained by constructing a simple [consultation](#), but it is often easier to express the criteria that records must meet than those that they must not meet.

The steps for creating a consistency query are identical to those for a [consultation](#), except for one difference: the choice of filters.

In the criteria entry interface, we find the classic tools ([see dedicated page](#)), with in addition a button:



It allows you to copy a selected criterion from the If... area to the Then... area or vice versa.

Change a query (Cohérence Clé GL Articles)

Extract inconsistent data related to the following rule :

If...

Match Not match

SHKCOO (F4201) = '00001'

Then...

Match Not match

SHDCTO (F4201) = 'SQ'

< Back Next > Cancel

Contrary to consultation, there are 2 zones to enter criteria:

- **IF ...**
- **Then...**




it's mandatory to enter **at least** a criterion in If... and one in Then...

Example

- Criterion If... ⇒ SHKCOO = '00001'.
- Criterion Then ⇒ SHDCTO = 'SQ'

Case 1

- Criterion If... set to Respected.
- Criterion Then... set on Respected ⇒ We get the records for which SHKCOO = '00001' and SHDCTO <> 'SQ'.



SHKCOO	SHDOCO	SHDCTO	SDLNID
Société doc	N° comman	Type com.	N° ligne (€
00001	210 SB		1,000
00001	210 SB		2,000
00001	210 SB		3,000
00001	210 SB		4,000
00001	210 SB		5,000
00001	251 CO		1,000
00001	257 SB		1,000
00001	257 SB		1,010
00001	257 SB		1,020
00001	257 SB		1,030

Case 2

- Criterion If... set to Respected.
- Criterion Then... positioned on Not respected ⇒ We retrieve the records for which SHKCOO = '00001' and SHDCTO = 'SQ'.

SHKCOO	SHDOCO	SHDCTO	SDLNID
Société doc	N° comman	Type com.	N° ligne (€
00001	121	SQ	1,000
00001	121	SQ	2,000
00001	121	SQ	3,000
00001	121	SQ	4,000
00001	121	SQ	5,000
00001	150	SQ	1,000
00001	151	SQ	1,000
00001	151	SQ	1,010
00001	151	SQ	1,020
00001	151	SQ	1,030
00001	151	SQ	1,040


Case 3

- Criterion If ... set to Not met.
- Criterion So... positioned on Respected ⇒ We retrieve the records for which SHKCOO <> '00001' and SHDCTO <> 'SQ'...

SHKCOO	SHDOCO	SHDCTO	SDLNID
Société doc	N° comman	Type com.	N° ligne (€
00200	250	CO	1,000
00200	255	CO	1,000
00200	256	SB	1,000
00200	803	ST	1,000
00200	2401	SO	1,000
00200	2401	SO	2,000
00200	2401	SO	3,000
00200	2401	SO	4,000
00200	2401	SO	5,000
00200	2401	SO	6,000
00200	2401	SO	7,000
00200	2401	SO	8,000

Case 4

- Criterion If ... set to Not met.
- Criterion Then... positioned on Not respected ⇒ We retrieve the records for which SHKCOO <> '00001' and SHDCTO = 'SQ' (in this case none)



The screenshot shows a software interface with a table. The table has four columns: SHKCOO (Société doc), SHDOCO (N° comman), SHDCTO (Type com.), and SDLNID (N° ligne). The interface includes a toolbar with icons for search, edit, delete, print, and view, and a search bar containing the text 'SDLNID'.

SHKCOO	SHDOCO	SHDCTO	SDLNID
Société doc	N° comman	Type com.	N° ligne (S

From: <https://vigilens.wiki/dokuwiki/> - **Vigilens Reporting Knowledge Garden**

Permanent link: https://vigilens.wiki/dokuwiki/doku.php?id=en:v8_0_0:designer:menus:accueil:nouvellerequete:coherence&rev=1594301034

Last update: **2020/07/09 15:23**

